Amendments to the Claims

Claims 1-12 (Canceled)

13. (Currently Amended) A header decompression apparatus for receiving a packet having a compressed header and decompressing the compressed header by referring to reference information decompressing a compressed header of a packet for transmission by referring to reference information being the same as reference information referred to for header compression by a transmitting side, said apparatus comprising:

a reference information manager for storing and managing said reference information;

a header decompressor, provided with the received packet, for carrying out header decompression by referring to the reference information stored in said reference information manager;

an error detector for detecting an error in the packet including the <u>header</u> decompressed <u>header</u> by said header decompressor;

a counter/storage for counting a number of packets having an error detected by said error detector from among the last W packets decompressed by said header decompressor; and

an update request unit for transmitting an update request for requesting update of said reference information stored in said reference information manager, based on the values counted by said counter/storage.

14. (Previously Presented) The header decompression apparatus according to claim 13, wherein

W is a predetermined value stored in said counter/storage, and said counter/storage counts the number of packets R having an error detected by said error detector from among the last W packets decompressed by said header decompressor, wherein W is an integer and R is an integer.

15. (Previously Presented) The header decompression apparatus according to claim 14, wherein

said update request unit determines, based on W and R counted by said counter/storage,

that the reference information stored in said reference information manager has errors when R is larger than a predetermined value.

16. (Previously Presented) The header decompression apparatus according to claim 15, wherein

the predetermined value is determined based on W.

17. (Previously Presented) A header decompression method for receiving a packet having a compressed header and decompressing the compressed header by referring to reference information, said method comprising:

a header decompressing step, provided with the received packet, of carrying out header decompression by referring to the reference information;

an error detecting step of detecting an error in the packet including the header decompressed in said header decompressing step;

a counting /storing step of counting a number of packets having an error detected in said error detecting step from among the last W packets decompressed in said header decompressing step; and

an update requesting step of transmitting an update request for requesting update of the reference information, based on the values counted in said counting/storing step.

18. (Previously Presented) The header decompression method according to claim 17, wherein

W is a predetermined value stored in said counting/storing step, and said counting/storing step counts the number of packets R having an error detected in said error detecting step from among the last W packets decompressed in said header decompressing step, wherein W is an integer and R is an integer.

19. (Currently Amended) The header decompression <u>methodapparatus</u> according to claim 18, wherein

said update requesting step determines, based on W and R counted in said

counting/storing step, that the reference information has errors when R is larger than a predetermined value.

20. (Previously Presented) The header decompression method according to claim 19, wherein

in said update requesting step, the predetermined value is determined based on W.

21. (Previously Presented) A computer-readable recording medium with a program recorded therein, the program being executed in a computer system for receiving a packet having a compressed header and decompressing the compressed header by referring to reference information, said program comprising:

a header decompressing step, provided with the received packet, of carrying out header decompression by referring to the reference information;

an error detecting step of detecting an error in the packet including the header decompressed in said header decompressing step;

a counting /storing step of counting a number of packets having an error detected in said error detecting step from among the last W packets decompressed in said header decompressing step; and

an update requesting step of transmitting an update request for requesting update of the reference information, based on the values counted in said counting/storing step.

22. (Previously Presented) A computer-readable recording medium according to claim 21, wherein

W is a predetermined value stored in said counting/storing step, and said counting/storing step counts the number of packets R having an error detected in said error detecting step from among the last W packets decompressed in said header decompressing step, wherein W is an integer and R is an integer.

23. (Previously Presented) The computer-readable recording medium according to claim 22, wherein

in said update requesting step determines, based on W and R counted in said counting/storing step, that the reference information has errors when R is larger than a predetermined value.

24. (Previously Presented) The computer-readable recording medium according to claim 23, wherein

in said update requesting step, the predetermined value is determined based on W.

25. (Previously Presented) A program executed in a computer system for receiving a packet having a compressed header and decompressing the compressed header by referring to reference information, said program comprising:

a header decompressing step, provided with the received packet, of carrying out header decompression by referring to the reference information;

an error detecting step of detecting an error in the packet including the header decompressed in said header decompressing step;

a counting /storing step of counting a number of packets having an error detected in said detecting step from among the last W packets decompressed in said header decompressing step; and

an update requesting step of transmitting an update request for requesting update of the reference information, based on the values counted in said counting/storing step.

26. (Previously Presented) The program according to claim 25, wherein,

W is a predetermined value stored in said counting/storing step, and said counting/storing step counts the number of packets R having an error detected in said error detecting step from among the last W packets decompressed in said header decompressing step, wherein W is an integer and R is an integer.

27. (Previously Presented) The program according to claim 26, wherein

said update requesting step determines, based on W and R counted in said counting/storing step, that the reference information has errors when R is larger than a

predetermined value.

28. (Previously Presented) The program according to claim 27, wherein in said update requesting step, the predetermined value is determined based on W.